

白鐵 "負公差" 定位銷 **庫存現貨**

材質: SUS303/304

直徑公差: +0/-0.02

直徑	長度
0.6	4

直徑	長度
0.8	3
	4
	5
	6
	7
	8
	9
	10
	12

直徑	長度
1	3
	4
	5
	6
	7
	8
	9
	10
	12
	14
	15
	16
	18
	20
	23
	25

直徑	長度
1.2	4
	4.5
	5
	6
	8
	10
	12
	14
	16
	18
	20
	22
	24

直徑	長度
1.3	10

直徑	長度
1.4	4
	5
	6
	8
	10
	12

直徑	長度
1.5	3
	4
	5
	6
	8
	10
	12
	14
	15
	16
	17
	18
	19
	20
	21
	22
	23
	25
	28
	30

直徑	長度
1.6	5
	6
	8
	10
	12

直徑	長度
1.7	5

直徑	長度
1.8	4
	5
	6
	8
	10
	12

直徑	長度
1.9	5
	6
	8
	9
	10
	12
	14
	16
	18
	20

白鐵 "負公差" 定位銷 **庫存現貨**

材質: SUS303/304

直徑公差: +0/-0.02

直徑	長度
2	3
	4
	4.5
	5
	6
	7
	8
	9
	10
	11
	12
	14
	15
	16
	17
	18
	19
	20
	21
	22
	23
	25
	26
	27
	28
	29
	30
	31
	32
	35
	40
	45

直徑	長度
2	48
	50
	55
	60
	65
	70
	75
	80
	90
	95
	100

直徑	長度
2.1	5

直徑	長度
2.2	10

直徑	長度
2.4	10

直徑	長度
2.5	4
	5
	6
	8
	10
	12
	14
	15
	16
	18
	20
	22
	25
	26
	28
	30
	32
	35
	40
	45
	50
	60
	65
	70
	80

直徑	長度
2.9	5

白鐵 "負公差" 定位銷 庫存現貨

材質: SUS303/304

直徑公差: +0/-0.02

直徑	長度
3	3
	4
	5
	6
	7
	8
	9
	10
	11
	12
	13
	14
	15
	16
	17
	18
	19
	20
	21
	22
	23
	24
	25
	26
	27
	28
	29
	30
	31
	32
	33
	34
	35

直徑	長度
3	36
	37
	38
	39
	40
	45
	50
	55
	60
	70
	80
	85
	90
	100

直徑	長度
3.4	5

直徑	長度
3.5	6
	8
	10
	12
	14
	15
	16
	18
	20
	25
	30
	35
	40
	45
	50

直徑	長度
4	4
	5
	6
	7
	8
	9
	10
	12
	13
	14
	15
	16
	17
	18
	19
	20
	25
	28
	30
	32
	35
	40
	45
	50
	60
	70
	80
	90
	100
	110
	120

白鐵 "負公差" 定位銷 庫存現貨

材質: SUS303/304

直徑公差: +0/-0.02

直徑	長度
5	5
	6
	8
	10
	12
	14
	15
	16
	18
	20
	22
	25
	26
	28
	30
	32
	35
	40
	45
	50
	60
	70
	80
	90
	100
	110
	120

直徑	長度
6	6
	8
	10
	12
	15
	16
	18
	20
	25
	30
	35
	40
	45
	50
	55
	59
	60
	70
	80
	90
	100
	110
	120

直徑	長度
8	8
	10
	15
	16
	20
	25
	30
	35
	40
	45
	50
	55
	60
	70
	75
	80
	85
	90
	100
	120

白鐵 "負公差" 定位銷 庫存現貨

材質: SUS303/304

直徑公差: +0/-0.03

直徑	長度
10	10
	14
	16
	18
	20
	25
	30
	35
	40
	45
	50
	60
	65
	70
	80
	90
	100

直徑	長度
12	14
	15
	16
	18
	20
	22
	25
	30
	35
	45
	50
	55
	60
	65
	70
	75
	80
	85
	90
	100
	120

直徑	長度
14	30
	35
	40
	45
	50

直徑	長度
16	8
	10
	12
	16
	20
	25
	30
	35
	40
	45
	50
	60

直徑	長度
18	30
	35
	40
	45
	50
	55
	60
	65
	70

直徑	長度
20	30
	35
	40
	45
	50
	60
	70
	80

直徑	長度
25	70
	80
	90