

負公差定位銷/ 軸承鋼

材質: SUJ2/52100

直徑公差: +0/-0.02

熱處理: HRC56-62

直徑	長度
1	4
	5
	6
	7
	8
	9
	10
	12
	15
	18
	20
	22
	24
	25
	26
	30
	35

直徑	長度
1.5	4
	5
	6
	7
	8
	9
	10
	12
	15
	17
	18
	25
	26
	30
	33

直徑	長度
1.6	5.1

直徑	長度
1.2	8

直徑	長度
2	2
	3
	4
	5
	6
	7
	8
	9
	10
	11
	12
	13
	14
	15
	16
	17
	18
	19
	20
	22
	24
	25
	26
	27
	28
	30
	32
	35
	40
	45
	50

直徑	長度
3	3
	4
	5
	6
	7
	8
	9
	10
	11
	12
	13
	14
	15
	16
	17
	18
	19
	20
	21
	22
	23
	24
	25
	26
	27
	28
	30
	32
	35
	38
	40
	50

*庫存眾多, 未能全放, 官方LINE洽詢ID:@sfptw

負公差定位銷/ 軸承鋼

材質: SUJ2/52100

直徑公差: +0/-0.02

熱處理: HRC56-62

直徑	長度
3	3
	4
	5
	6
	7
	8
	9
	10
	11
	12
	13
	14
	15
	16
	17
	18
	19
	20
	21
	22
	23
	24
	25
	26
	27
	28
	30
	32
	35
	38
	40

直徑	長度
3	50
	55
	60
	70
	86

直徑	長度
3.5	5
	10
	12
	15
	17
	18
	20
	22
	24
	30
	50

直徑	長度
4	4
	5
	6
	7
	8
	10
	11
	12
	14
	15
	16
	16.5
	18
	20
	25
	30
	36
	50
	55
	60

直徑	長度
4.5	10
	12
	15
	20
	40
	50
	60

直徑	長度
4.05	10
	13

*庫存眾多, 未能全放, 官方LINE洽詢ID:@sfptw

負公差定位銷/ 軸承鋼

材質: SUJ2/52100

直徑公差: +0/-0.02

熱處理: HRC56-62

直徑	長度
5	5
	6
	7
	8
	9
	10
	12
	14
	15
	16
	18
	20
	22
	25
	26
	28
	30
	32
	35
	38
	40
	45
	50
	55
	60

直徑	長度
6	6
	7
	8
	10
	12
	15
	16
	18
	20
	25
	30
	32
	35
	40
	45
	50
	55
	60

直徑	長度
7	7
	9
	10
	11
	12
	13
	14
	15
	16
	18
	20
	30

直徑	長度
8	10
	12
	14
	15
	16
	18
	20
	21
	25
	26
	30
	35
	40
	55

直徑	長度
9	9
	10
	12
	14
	15
	16
	18
	20
	30

直徑	長度
10	11
	20
	24
	25
	30
	40
	55
	70
	180

直徑	長度
11	11
	12
	13
	15
	16
	18
	20

直徑	長度
12	20
	25
	30
	40
	60
	70

直徑	長度
13	15
	60
直徑	長度
15	20
	30